



# BSPT Threads - British Standard Pipe Tapered Threads Whitworth Tapered Pipe Thread DIN 2999

Specifications of International Thread Standards

Male Thread Diameter	Female Thread Diameter	Pipe Minor Diameter mm	Pipe Major Diameter mm	Tapping Drill Size mm	TPI	Pitch mm
R 1/16"	Rp 1/16"	3	7,723	6,561	28	0,907
R 1/8"	Rp 1/8"	6	9,728	8,566	28	0,907
R 1/4"	Rp 1/4"	8	13,157	11,445	19	1,337
R 3/8"	Rp 3/8"	10	16,662	14,950	19	1,337
R 1/2"	Rp 1/2"	15	20,995	18,631	14	1,814
R 3/4"	Rp 3/4"	20	26,441	24,117	14	1,814
R 1"	Rp 1"	25	33,249	30,291	11	2,309
R 1 1/4"	Rp 1 1/4"	32	41,910	38,952	11	2,309
R 1 1/2"	Rp 1 1/2"	40	47,803	44,845	11	2,309
R 2"	Rp 2"	50	59,614	56,656	11	2,309
R 2 1/2"	Rp 2 1/2"	65	75,184	72,226	11	2,309
R 3"	Rp 3"	80	87,884	84,926	11	2,309
R 4"	R 4"	100	113,030	110,072	11	2,309
R 5"	Rp 5"	125	138,430	135,472	11	2,309
R 6"	Rp 6"	150	163,830	160,872	11	2,309

Interwork Sdn. Bhd.

**MILLION INTERWORK SDN. BHD**  
 Lot 315, Jalan PKNK 3, Kawasan Perindustrian Sungai Petani,  
 08000 Sungai Petani, Kedah, Malaysia.  
 Tel: +60-4-441 4288 Fax: +60-4-442 9092  
<http://www.million.url.tw>