



ISO Metric Coarse Thread DIN 13

Specifications of International Thread Standards

Nominal Diameter	Pitch	Tapping Drill Size
M	mm	mm
1,0	0,25	0,75
1,1	0,25	0,85
1,2	0,25	0,95
1,4	0,30	1,10
1,6	0,35	1,25
1,8	0,35	1,45
2,0	0,40	1,60
2,2	0,45	1,75
2,5	0,45	2,05
3,0	0,50	2,50
3,5	0,60	2,90
4,0	0,70	3,30
4,5	0,75	3,70
5,0	0,80	4,20
6,0	1,00	5,00
7,0	1,00	6,00
8,0	1,25	6,80
9,0	1,25	7,80
10,0	1,50	8,50
11,0	1,50	9,50
12,0	1,75	10,20
14,00	2,00	12,00
16,00	2,00	14,00
18,00	2,50	15,50
20,00	2,50	17,50
22,00	2,50	19,50
24,00	3,00	21,00
27,00	3,00	24,00
30,00	3,50	26,50
33,00	3,50	29,50
36,00	4,00	32,00
39,00	4,00	35,00
42,00	4,50	37,50
45,00	4,50	40,50
48,00	5,00	43,00
52,00	5,00	47,00
56,00	5,50	50,50
60,00	5,50	54,50
64,00	6,00	58,00

SHINING JINS ENTERPRISE CO., LTD.

No.107, Lane 530, Sec. 1, Guoji Road., Taoyuan Dist., Taoyuan City 330, Taiwan.

Tel: +886-3-361 0638 Fax: +886-3-367 752792

<http://www.shiningjins.com>

E-mail: sales1@shiningjins.com

