



ISO Metric Coarse Thread DIN 13

Specifications of International Thread Standards

Nominal Diameter M	Pitch mm	Tapping Drill Size mm
1,0	0,25	0,75
1,1	0,25	0,85
1,2	0,25	0,95
1,4	0,30	1,10
1,6	0,35	1,25
1,8	0,35	1,45
2,0	0,40	1,60
2,2	0,45	1,75
2,5	0,45	2,05
3,0	0,50	2,50
3,5	0,60	2,90
4,0	0,70	3,30
4,5	0,75	3,70
5,0	0,80	4,20
6,0	1,00	5,00
7,0	1,00	6,00
8,0	1,25	6,80
9,0	1,25	7,80
10,0	1,50	8,50
11,0	1,50	9,50
12,0	1,75	10,20
14,00	2,00	12,00
16,00	2,00	14,00
18,00	2,50	15,50
20,00	2,50	17,50
22,00	2,50	19,50
24,00	3,00	21,00
27,00	3,00	24,00
30,00	3,50	26,50
33,00	3,50	29,50
36,00	4,00	32,00
39,00	4,00	35,00
42,00	4,50	37,50
45,00	4,50	40,50
48,00	5,00	43,00
52,00	5,00	47,00
56,00	5,50	50,50

MILLION INTERWORK SDN. BHD

Lot 315, Jalan PKNK 3, Kawasan Perindustrian Sungai Petani,

08000 Sungai Petani, Kedah, Malaysia.

Tel: +60-4-441 4288 Fax: +60-4-442 9092

<http://www.million.url.tw>



ISO Metric Coarse Thread DIN 13

Specifications of International Thread Standards

Nominal Diameter M	Pitch mm	Tapping Drill Size mm
60,00	5,50	54,50
64,00	6,00	58,00
68,00	6,00	62,00